# CALIB Compact air-launch ice beacon Air deployable Innovative and robust design Instrumentation packages available METOCEAN SYSTEMS

The Compact Air Launched Ice Beacon (CALIB) is an Argos-reporting mini beacon that may be launched from either a fixed or rotary-wing aircraft. The CALIB buoys collect meteorological data in support of weather forecasting in polar climates and it is also used for ice flow tracking.

The standard CALIB is equipped with an Ice Surface Temperature Sensor (SST) and an alkaline battery pack for longevity. Additional sensors are available.





# **TECHNICAL SPECIFICATIONS**

**PHYSICAL** 

 Hull Diameter
 5" (120 mm)

 Height
 36.10" (917 mm)

 Mass (in air)
 8.20 kg (18 lbs)

CONSTRUCTION

Hull Phenotic tube
Colour White

**LAUNCH SPEED** 

0 to 200 knots Indicated Air Speed (IAS) maximum

LAUNCH ALTITUDE

152.40 m to 2,438.40 m (500 ft to 8,000 ft)

**OPERATION** 

Air Temperature -50°C to 55°C (-58°F to 131°F)

Sunlight Direct exposure

Operating Life (alkaline) 3 months (at  $\geq$  -30°C)

Operating Life (lithium) 12 months (at  $\geq$  -40°C)

Battery Pack Size 20 D-cells

Storage Life (alkaline) 2 years (minimum) Storage Life (lithium) 5 years (minimum)

**SURVIVAL** 

Air Temperature -60°C to 55°C (-76°F to 131°F)

**ELECTRONICS\*** 

Iridium Telemetry 9602N Short Burst Data

transceiver

**SENSORS** 

Ice Surface Temperature YSI Model 44031

Battery Voltage Precision resistive divider

Barometric Pressure Valsala PMB-100 Pressure Sensor

### **HEAD OFFICE**

MetOcean Telematics 21 Thornhill Drive Dartmouth, Nova Scotia Canada B3B 1R9 sales@metocean.com

# **UNITED STATES**

MetOcean Telematics 1750 Tysons Blvd Suite 1500, Office 1547 McLean, VA 22102 sales@metocean.com

+1 844 728 2868

## **UNITED KINGDOM**

MetOcean Telematics Hilldale Farm Titchfield Lane, Wickham, UK P017 5NZ sales@metocean.com

+44 1489 888 555

### CANADA

MetOcean Telematics 2 Gurdwara Rd Suite 608 Ottawa, Ontario Canada K2E 1A2 sales@metocean.com

+1 613 702 3196

<sup>\*</sup>Optional ARGOS Satellite Transmitter available