

EDGE™



TRACKING & MONITORING

Iridium Edge™

Dependable global connectivity

Iridium Edge™, a ready-to-go, reliable and cost effective satellite communications device that expands connectivity beyond cellular limits. Deliver more value to customers by leveraging your existing M2M solutions for telematics, safety and other remote monitoring applications.

Fast time-to-market is a critical component in today's highly competitive communications environment. Iridium Edge™ is a satellite add-on enabling dual-mode capability and reducing the cost, uncertainties and complications associated with hardware development, manufacture and certification of the satellite-specific terminal.



Key Markets:

- Maritime
- Remote Monitoring
- SCADA
- Asset Tracking
- Fleet Management

EDGE™

Key Features of Iridium Edge™ :

- **Hardware-Ready Device** for simple, low risk integration
- **Low-Cost Device** for affordable customer adoption
- **Satellite Add-On** for truly global coverage
- **Ready-To-Install** for quick time-to-market
- **Robust Power Supply** for industrial installations
- **Certified** in key geographic markets
- **180° Line of Sight** for compromised, partially blocked locations
- **Iridium Short Burst DataSM** (SBDSM) modem for Iridium's superior network advantages

TECHNICAL SPECIFICATIONS

NETWORK

- Frequency: 1616 – 1626.5 MHz
- Message Size: 270 bytes (Receive), 340 bytes(Transmit)
- SBD Transceiver: Iridium 9602N
- Antenna: Integrated Iridium® certified antenna

MECHANICAL

- Dimensions: 130 mm (L) x 80 mm (W) x 30 mm (H)
- Ingress Protection: IP 67
- Side and Bottom Cable Exits
- Connector: M12-8 pin male, terminated on 20cm pigtail cable
- Installation Options: Pole, Screw, Tape

INTERFACES

- RS232 AT Command Interface
- On/Off Control Lines

POWER

- Power Supply: (9-32V), SAE J1455 Load Dump Protected
- Maximum Power: 1.6W (Peak for Short Transmit Burst)
- Low Power Modes: < 200uA
- Reverse Polarity Protection

ENVIRONMENTAL

- Operating Temperature Range: -40C to 85C
- Storage Temperature Range: -40C to 85C
- Vibration: SAE J1455, Section 4.10

CERTIFICATIONS

- Iridium® Satellite Network Certification
- RoHS Compliant
- FCC, IC, CE, Australia Approvals

HEAD OFFICE

MetOcean Telematics
21 Thornhill Drive
Dartmouth, Nova Scotia
Canada B3B 1R9
sales@metocean.com

+1 902 468 2505

UNITED STATES

MetOcean Telematics
1750 Tysons Blvd
Suite 1500, Office 1547
McLean, VA 22102
sales@metocean.com

+1 844 728 2868

UNITED KINGDOM

MetOcean Telematics
Hilldale Farm
Titchfield Lane,
Wickham, UK PO17 5NZ
sales@metocean.com

+44 1489 888 555

CANADA

MetOcean Telematics
2 Gurdwara Rd Suite 608
Ottawa, Ontario
Canada K2E 1A2
sales@metocean.com

+1 613 702 3196