

MissionLINK™

- Delivering critical satellite communications to keep you connected regardless of the landscape
- Providing 100% global coverage you can depend on
- Enabling essential communications for critical operations



MissionLINK utilizing Iridium CertusSM gives your critical operation global communications coverage regardless of the landscape. It is the solution to depend on for essential communications wherever your mission takes you. Whether you operate as part of a deployed force or an individual user, this commercialized, military-grade solution is designed to meet your unique challenges through a simple, adaptable and robust design.

MissionLINK on Iridium operates using Iridium CertusSM broadband services over a network of 66 satellites that cover 100% of the globe. The solution utilizes this robust network service to provide highly reliable, mobile and essential voice, text and web communications.

MULTI-SERVICES PLATFORM

- IP data sessions up to 700kbps (down)/352kbps (up)
- Streaming up to 256kbps
- 3 high quality voice lines
- Location tracking
- PTT ready





TECHNICAL SPECIFICATIONS

Size	12 in x 9 in x 3 in (30.5 cm x 22.9 cm x 7.6 cm)
Weight	7.2 lb. (3.3 kg)
Power	12 VDC input, 11A max (7A avg.) includes powering external HGA-2 Antenna
Connectors	Front: RJ-45 LAN (3) Class 2 PoE RJ-45 WAN (1) for cellular connection RJ-14 POTS Rear: DC Power Input (10-32V) MIL-STD-1275D DC Power Input, +12V Regulated GPIO (RS-232, +12V out, DISTRESS, Radio Gateway, GPIO) TNC Connector, RF connection to Antenna Wi-Fi reverse SMA SIM slot
Mechanical Vibration and Shock	MIL-STD-810G, Test Method 514.6, Proc. 1, Category 20, Annex D MIL- STD-810G, Test Method 516.6,

ANTENNA SPECIFICATIONS

High-gain, electronic phased array antenna to enable the fastest upload and download speeds to cover any vessel communications need from safety services to operational reporting and logging	
Size	14 in x 4 in h (35.6 cm dia. x 10.2 cm h)
Weight	7 lb. (3.2 kg)
Power	Directly powered by the terminal at 24 VDC
Operating Temperature	-30 to +55 degrees C
Mechanical Vibration and Shock	MIL-STD-810G, Test Method 514.6, Proc. 1, Category 20, Annex D MIL-STD-810G, Test Method 516.6, Proc. IV

HEAD OFFICE

MetOcean Telematics
21 Thornhill Drive
Dartmouth, Nova Scotia
Canada B3B 1R9
sales@metocean.com

+1 902 468 2505

UNITED STATES

MetOcean Telematics
1750 Tysons Blvd
Suite 1500, Office 1547
McLean, VA 22102
sales@metocean.com

+1 844 728 2868

UNITED KINGDOM

MetOcean Telematics
Hilldale Farm
Titchfield Lane,
Wickham, UK PO17 5NZ
sales@metocean.com

+44 1489 888 555

CANADA

MetOcean Telematics
2 Gurdwara Rd Suite 608
Ottawa, Ontario
Canada K2E 1A2
sales@metocean.com

+1 613 702 3196