

# VesseLINK™ 200



## Same uninterrupted coverage from pole-to-pole, smaller antenna

Thales VesseLINK provides global satellite coverage for maritime communications. With uninterrupted coverage from pole to pole, it is the solution to depend on for essential communications. Suitable for ships or fleets of any size, VesseLINK easily integrates with your existing equipment to fully digitize your vessel. VesseLINK comes with an intuitive, user-friendly interface and can be quickly integrated into existing vessels or new fleets. It also includes built-in upgradeability to future-proof your investment and ensures peak speed and performance.

VesseLINK operates using Iridium Certus broadband services over a network of 66 satellites that cover 100% of the globe, including deep oceans and poles. The solution utilizes this robust network service to provide highly reliable, mobile and essential voice, text and web communications for captain and crew.

### Key Features

- Certus 200 Service (176 kpbs Up/Down)
- Robust, light-weight communications for at sea operations
- 100% global satellite coverage and low latency for critical data and voice communications
- Dependable maritime satcoms, from pole-to-pole
- Easily integrates VSAT with built-in preferred routing





## TECHNICAL SPECIFICATIONS

**Height:** 2.3 inches (5.8 cm)

**Width:** 12 inches (30.5 cm)

**Depth:** 9 inches (22.9 cm)

**Weight:** 7.5 pounds (3.4 kg)

### Power Options

**Option 1:** 10–32 VDC

**Option 2:** AC/DC supply with 12 VDC  
(65 watt nominal/120 watt max)

**IP Rating:** IP31

**Front Connectors:** RJ-45 LAN (3) Class 2 PoE  
RJ-45 WAN (1) for cellular, VSAT and other  
IP connections, RJ-14 POTS (2 independent  
phone lines)

**Rear Connectors:** DC Power Input (10–32V)  
MIL-STD-1275D, DC Power Input  
(+12V Regulated), GPIO (RS-232, +12V out,  
Emergency, Radio Gateway, Discrete I/O),  
TNC – RF connection to Antenna,  
Wi-Fi – Reverse SMA, SIM card slot

### Mechanical Vibration and Shock:

MIL-STD-810G w/Change 1, Test Method  
514.7, Category 4

## ANTENNA SPECIFICATIONS

Low-gain omnidirectional antenna to enable the fastest upload and download speeds to cover any land communications need from safety services, tracking and location services, out-of-band management to operational reporting and data transfers.

**Size:** 5 inches dia. x 5.5 inches h  
(12.5 cm dia. x 14 cm h)

**Weight:** <0.7 kg/1.5 lbs

**Power:** Directly powered by the terminal  
at 24 VDC

**IP Rating:** IP67

**Operating Temperature:** -40 to +55° C

### Mechanical Vibration and Shock:

MIL-STD-810G w/Change 1, Test Method  
514.7, Category 4

### HEAD OFFICE

MetOcean Telematics  
21 Thornhill Drive  
Dartmouth, Nova Scotia  
Canada B3B 1R9  
sales@metocean.com

+1 902 468 2505

### UNITED STATES

MetOcean Telematics  
1750 Tysons Blvd  
Suite 1500, Office 1547  
McLean, VA 22102  
sales@metocean.com

+1 844 728 2868

### UNITED KINGDOM

MetOcean Telematics  
Hilldale Farm  
Titchfield Lane,  
Wickham, UK PO17 5NZ  
sales@metocean.com

+44 1489 888 555

### CANADA

MetOcean Telematics  
2 Gurdwara Rd Suite 608  
Ottawa, Ontario  
Canada K2E 1A2  
sales@metocean.com

+1 613 702 3196